



Interactive digital noticeboard

- **No more paper flyers** in halls
- **Real-time** resident information **without going on site**
- Communicate unique messages to each noticeboard
- Scroll buttons



INTERACTIVE DIGITAL NOTICEBOARD, 15-inch screen, external fitting, surface mounted



GOOD TO KNOW

On the noticeboard, quick cover removal:
adjust contrast,
reset noticeboard



PRODUCT ADVANTAGE

Make a survey among your residents with the poll function

DIGITAL NOTICEBOARD PRODUCT RANGE

INTERACTIVE DIGITAL NOTICEBOARD, 15-INCH SCREEN	
11-0107	Indoor version - surface mounted
DIGITAL NOTICE BOARD, 15-INCH SCREEN	
11-0102	To be mounted to a post or a door (flush back box required, not provided by COGEELEC) - Flush fitted
11-0103	Outdoor version, waterproof and regulated - Surface mounted
INTRA BOX DATA ECO	
06-0208	Intrabox notice board: 1 digital notice board - interactive (11-0107) + 1 transmission module with data, unlimited data synchronisation for 15 years



Remote online management
www.intratone.info

DESCRIPTION

CONNECTION	
4G-IP module	✓
Max number of notice boards per module	1
MANAGEMENT / UPDATES	
Through the www.intratone.info website	✓
File format for uploads	PDF, Excel, Word
Max file size	8 Mo
Unlimited updates	✓
MOUNTING	
Surface mounted, indoor (interactive)	11-0107
Flush fit / indoor	11-0102
Saillie / en extérieur	11-0103
FINISH	
Anthracite, sanded	✓
SECURITY	
Protection class	IKo8
Safety glass	Thick. 10 mm

TECHNICAL CHARACTERISTICS

POWER SUPPLY

The digital notice board - 24 V DC

2 A - for indoor version

3A - for the outdoor version

WIRING

Notice board - 4G module

4 wires (2 twisted pairs) - Ø 8/10e - Max distance: 100 m

DIMENSIONS (L x H x D)

Indoor version - Surface mounted **348 x 525 x 28 mm**

Flush fit version that can be integrated **350 x 510 x 42 mm**

Outdoor version - Surface mounted **348 x 549 x 49 mm**

ENVIRONMENT

Digital notice board, indoor version :

Operating temperature **-10°C to + 45°C**

Protection class **IP52**

Surface mounted / outdoor :

Operating temperature **-20°C to + 60°C**

Watertight - Outdoor fitting

SIMPLIFIED SCHEMATIC

