



# V4 VIDEO INTERCOM

- **Hands-free** proximity reader
- Inductive hearing loop
- Intercom fixed on swivel hinge

**V4 VIDEO INTERCOM** with name scroll, invisible pinhole camera with 12-button backlit coded keypad and hands-free proximity reader - flush mounted



Stainless steel finish



Brass finish



With integrated key safe

## RANGE

INTERCOM ONLY	
02-0182	Stainless steel finish
02-0183	Brass finish
FULL 200-USER KIT : 1 INTERCOM + 1 CENTRAL UNIT 1-DOOR (03-0102)	
02-0184	Stainless steel finish
02-0186	Brass finish
FULL 1000-USER KIT : 1 INTERCOM + 1 CENTRAL UNIT 2-DOORS (03-0101)	
02-0185	Stainless steel finish
02-0187	Brass finish

ACCESSORIES	
12-0108	Rain shield for V4 video intercom - stainless steel finish
12-0160	Surface box for 4V video intercom (02-0182, 02-0184 and 02-0185) - surface mounted - stainless steel finish
12-0178	Surface box for 4V video intercom (02-0183, 02-0186 and 02-0187) - surface mounted - brass finish



Remote online management  
[www.intratone.info](http://www.intratone.info)

Don't forget to add your service package!



## DESCRIPTION

CENTRAL UNIT	1 door	2 doors
	03-0102	03-0101
<b>Max number of apartments managed</b>	<b>max. 200</b>	<b>max. 1000</b>
<b>SYSTEM</b>		
Number of relays	1(+3)	2(+2)
<b>CONNECTION</b>		
4G-IP module	✓	✓
<b>4G-IP MODULE CHARACTERISTICS</b>		
Remote 4G-IP module	✓	✓
Possibility to add a remote camera	✓	✓
Max number of intercoms per module	1 video	1 video
<b>Service package included</b>	Upon request	Upon request
<b>ACCESS CONTROL EQUIPMENT</b>		
Coded keypad	✓	✓
Hands-free proximity reader	✓	✓
Inductive hearing loop	✓	✓
<b>MOUNTING</b>		
Flush-fit	✓	✓
Swivel hinges	✓	✓
<b>FINISHES</b>		
Stainless steel	✓	✓
Brass	✓	✓

Call length	40 sec.
Customizable welcome message (64 characters - fixed or scrolling)	✓
Accelerated alphabetical research	✓
Braille keypad	✓
High contrast yellow rings around buttons	✓
Suitable for public access buildings	✓
Call sheet display (apartments) during time slots	✓
Display : 2 lines of 16 characters	✓
Operational messages : (call in progress...)	✓
Speech synthesis	✓
Anti-disturbance <sup>(1)</sup>	✓
Sound level adjustment without dismantling	✓
Automatic call return if no answer	✓

(1) System ensuring that a resident is not disturbed by repetitive calls

## TECHNICAL CHARACTERISTICS

## POWER SUPPLY

Central unit **12 VDC 5A - 24 VDC 2,5A**

## WIRING

**1 DOOR CENTRAL UNIT 03-0102**

4G-IP module - Central unit

**4 wires (2 twisted pairs) - Ø 8/10e - Max distance: 100m**

Central unit - Intercom

**4 wires (2 twisted pairs) - Ø 8/10e - Max distance: 100m**

Intercom - 4G-IP module

**4 wires (2 twisted pairs) - Ø 8/10e - Max distance: 100m**

**2-DOORS CENTRAL UNIT 03-0101**

4G-IP module - Central unit

**6 wires (3 twisted pairs) - Ø 8/10e - Max distance: 100m**

Central unit - Intercom

**6 wires (3 twisted pairs) - Ø 8/10e - Max distance: 100m**

Intercom - 4G-IP module

**2 wires (1 twisted pairs) - Ø 8/10e - Max distance: 100m**

## DIMENSIONS (L x H x D)

**INTERCOM**

**150 x 300 x 9 mm**

**WALL BOX**

**126 x 274 x 45 mm**

**SURFACE BOX**

**155.50 x 305.50 x 67 mm**

**RAIN SHIELD**

**155.50 x 305.50 x 35 mm**

## ENVIRONMENT

Working temperature

**-20° C to +60° C**

Protection class **IP54**

**Outside mounting**

## SIMPLIFIED SCHEMATIC

